

Waterblast  
hoses, fittings  
and ferrules



# Waterblasting High pressure cleaning



Fluiconnecto by Manuli provides an extensive range of products and solutions for virtually all applications in hydraulics. In addition Fluiconnecto offers a complete range of waterblast hoses, fittings and ferrules designed specifically for high pressure.

## High performance

- thermoplast or steel spirals
- compactness and flexibility
- pressure rated up to 1450 bar

## Applications

- descaling
- concrete and coatings removal
- hydro demolition
- roughening of asphalt and concrete
- other industrial uses

## Manuli Goldenblast and Blastlock

- integrated solution: Goldenblast hoses and Blastlock fittings
- 4 and 6 steel spirals
- developed for extreme pressures and operating conditions
- meeting international standards

## Jetpower thermoplast

- low weight
- high flexibility
- long lengths

## Recommended fluids

- water
- water soap emulsion

# GOLDENBLAST™



PART. REF.	HOSE SIZE				R.O.D.		O.D.		bar MAX W.P.		BURST PRESSURE		MIN. BEND RADIUS		kg WEIGHT		FITTING
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft		

H10072010	10	-06	3/8	17,6	0,69	20,2	0,80	750	10870	1875	27190	180	7,09	700	0,47	BL+M01700-06
H10072A12	12	-08	1/2	20,4	0,80	23,0	0,91	750	10870	1875	27190	220	8,66	820	0,55	BL+M01700-08

# GOLDENBLAST™/PLUS



	HOSE SIZE				R.O.D.		O.D.		bar MAX W.P.		BURST PRESSURE		MIN. BEND RADIUS		kg WEIGHT		FITTING
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft		

H10066010	10	-06	3/8	17,4	0,69	20,0	0,79	1250	18120	3125	45320	230	9,06	800	0,54	BL+M01700-06
H10066A12	12	-08	1/2	21,5	0,85	24,1	0,95	1100	15950	2750	39880	230	9,06	1110	0,75	BL+M01700-08
H10066019	19	-12	3/4	29,0	1,14	32,0	1,26	1000	14500	2500	36250	250	9,84	1730	1,16	BL+M01700-12
H10066025	25	-16	1	35,1	1,38	38,1	1,50	700	10150	1750	25370	250	9,84	2040	1,37	BL+M01500-16

# GOLDENBLAST™/SIX



	HOSE SIZE				R.O.D.		O.D.		bar MAX W.P.		BURST PRESSURE		MIN. BEND RADIUS		kg WEIGHT		FITTING
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft		

H10067012	12	-08	1/2	25,9	1,02	28,9	1,14	1450	21030	3625	52570	250	9,84	1880	1,26	BL+M01800-08
H10067019	19	-12	3/4	32,4	1,28	35,4	1,39	1350	19580	3375	48950	280	11,02	2630	1,77	BL+M01800-12

# JETPOWER Thermoplast

PART. REF.	HOSE SIZE				R.O.D.		O.D.		bar MAX W.P.		BURST PRESSURE		MIN. BEND RADIUS		kg WEIGHT		FITTING
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft		

0475-04	6	-04	1/4	14,5	0,571	1120	16240	2800	40600	40	1,57	253	0,196		M017200-04
0475-06	10	-06	3/8	18,8	0,74	1120	16240	2800	40600	90	3,54	389	0,261		M017200-06



**Manuli Fluiconnecto (HEBU)**  
 Van der Giessenweg 9  
 2921 LP Krimpen a/d IJssel  
 Tel. +31 (0)180 511 411  
 Fax. +31 (0)180 510 515  
 info@fluiconnecto.nl  
 www.fluiconnecto.com

